

SLink
Cable

1-1/4"R L PE

SL 114R L PE



This product used for mobile network and telecommunication equipment

Material and dimensions

Inner conductor	Copper tube	Ø 13.1 mm
Dielectric	Foam PE	Ø 32.5 mm
Outer conductor	Corrugated copper(Annularly)	Ø 35.8 mm
Jacket	PE, Black, UV resistant, Halogen free	Ø 39.5 mm
Ink marking: metric length	RosenbergerSLink™_SL 114R_L_PE_50Ω_ _ _ _ (DD+MM +SS+YY+NNNNN)_ _ _ _ _XXXXm	

Documents

UV resistance	GB/T 2423.24-1995; EN 50289-4-17, Method A
---------------	--

Electrical Specification

Impedance	50 ± 1 Ω
Relative Velocity of Propagation	89%
Capacitance	75 pF/m
Inductance	0.190 µH/m
Maximum Operating Frequency	3.5 GHz
Cut-off Frequency	3.7 GHz
Peak Power Rating	200 kW
Insulation Resistance	≥ 10 GΩ x km
DC Breakdown Voltage	10000V
Jacket Spark Test Voltage	10000 Vrms

Environmental Specification

Installation Temperature	-40°C to +60°C
Operating Temperature	-55°C to +85°C
Storage Temperature	-70°C to +85°C
RoHS	compliant

Mechanical Specification

Cable weight (nominal)	770 kg/km
Tensile strength	2500 N
Min. bending radius (single)	200 mm
Min. bending radius (repeated)	380 mm
Number of bends, minimum (typical)	15 (50)
Bending moment	50 Nm

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG
RF_35/05.10/6.0

Technical Data Sheet

Rosenberger

SLink
Cable

1-1/4"R L PE

SL 114R L PE

Flat plate crush strength 20 N/mm
Recommended hanger spacing 1.2 m

Standard Conditions

Attenuation, Ambient Temperature 20°C
Average Power, Ambient Temperature 40°C
Average Power, Inner Conductor Temperature 100°C

Return Loss

Return loss(Band A) ≤ -24dB 800 to 1000MHz
Return loss(Band B) ≤ -24dB 1700 to 1900MHz
Return loss(Band C) ≤ -24dB 1900 to 2200MHz
Return loss(Band D) ≤ -24dB 2200 to 2500MHz
Return loss(Band E) ≤ -21dB 2500 to 3000MHz

Attenuation

Frequency (MHz)	Attenuation (dB/100m)	Average power (KW)
100	0.80	13.4
200	1.15	9.31
300	1.55	7.17
400	1.72	6.03
450	1.83	5.50
800	2.47	3.90
900	2.64	3.70
1000	2.80	3.50
1800	3.96	2.40
2000	4.23	2.30
2200	4.48	2.20
2500	4.84	2.03
2700	5.19	1.86
3000	5.42	1.73

Maximum attenuation value shall be 105% of the nominal attenuation value
Other frequencies on request

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Check	Approved	Date	Rev.	Engineering change number	Name	Date
Feifei	23/11/11				f	15-0004	huanghuan	30/09/15
Rosenberger Hochfrequenztechnik GmbH & Co. KG, Germany Tel.: +49 8684 18-0 Fax: +49 8684 18-499 www.rosenberger.de email: info@rosenberger.de						Rosenberger Asia Pacific Electronic Co., Ltd., China Tel.: +86 10 80481995 Fax: +86 10 80497052 www.rosenbergerap.com email:info@rosenbergerap.com		Page 2 / 2